PATRIOT VIPER ELITE 5 RGB DDR5 16GB (1X16GB) 5600MHz KIT



Get ready to blow away the competition with Viper Gaming's newest high-speed DDR5 series: the Viper Elite 5. Featuring high transfer speeds, high capacities and tuned support for XMP 3.0 and EXPO profiles, the Viper Elite 5 offers superior DDR5 performance and stability built for mainstream gamers, tech enthusiasts and content creators.

With a unique high-performance white aluminum heatshield, the Viper Elite 5 offers a sharp, metallic aesthetic that stands out amongst its neighboring system components and competitors. The Viper Elite 5 also offers a full-spectrum RGB lightbar for a perfect combination of good looks and strong performance.

Backed by a limited lifetime warranty and built with best-in-class materials, the Viper Elite 5 is 100% hand-tested on the latest Intel DDR5 platform for quality assurance and reliability on high performance to offer peace of mind for all users

PRODUCT INFORMATION

PATRIOT INV. NUMBER:	PVER516G56C38W
DESCRIPTION:	PATRIOT VIPER ELITE 5 RGB DDR5 16GB (1X16GB) 5600MHz KIT
CERTIFICATIONS/SAFETY:	CE/FCC/RoHS/BSMI/UKCA
PRODUCT WARRANTY:	Limited Lifetime Warranty
UNIT UPC:	4711378425468
UNIT WEIGHT:	0.1 lbs /46 g
UNIT DIMENSIONS:	0.27"(L) x 5.23"(W) x 1.73"(H) 0.7 cm (L) x 13.3 cm (W) x 4.4 cm (H)
PACKAGING TYPE:	Retail Box
PACKAGING WEIGHT:	0.34 lbs / 149 g
PACKAGING DIMENSIONS:	0.79"(L) x 7.08"(W) x 6.24"(H) 2.03 cm (L) x 17.99 cm (W) x 15.87 cm (H)
MASTER CARTON WEIGHT:	19.7 lbs / 8.9 kg
MASTER CARTON DIMENSIONS:	22.63"(L) x 18.7"(W) x 7.87"(H) 57.5 cm (L) x 47.5 cm (W) x 20 cm (H)
UNITS PER INNER CARTON:	10
UNITS PER MASTER CARTON:	60

FEATURES:

- Series: Viper Elite 5 RGB DDR5 series
- Edition: White Heatshield
- Aluminum heat spreader with unique and specific design element
- Feature Overclock: XMP 3.0 & EXPO overclocking supported
- Compatibility: Tested across latest DDR5 platforms for reliably on high performance
- Limited lifetime warranty

SPECIFICATIONS:

- On-Die ECC
- Thermal sensor
- Capacity: 16GB (1 x 16GB)
- Base Frequency: PC5-38400 (4800MHz)
  - Base Timings: 40-40-40-77
  - Base Voltage: 1.1V
- Tested Frequency XMP Profile 1: PC5-44800 (5600MHz)
  - Tested Timings: 38-48-48-78
  - Tested Voltage for XMP Profile 1: 1.35V
- Tested Frequency XMP Profile 2: PC5-41600 (5200MHz)
  - Tested Timings: 40-40-40-76
  - Tested Voltage for XMP Profile 2: 1.35V
- Tested Frequency EXPO Profile 1: PC5-44800 (5600MHz)
  - Tested Timings: 38-48-48-78
  - Tested Voltage for EXPO Profile 1: 1.35V
- Tested Frequency EXPO Profile 2: PC5-41600 (5200MHz)
  - Tested Timings: 40-40-40-76
  - Tested Voltage for EXPO Profile 2: 1.35V
- RGB Sync with ASUS/ASRock/MSI/Gigabyte motherboard (please check with motherboard vendor for more info)
- Viper Exclusive RGB APP